

Composition Mounts



QMSC A 12" x 12" Composition Mount

- Designed for Quick & Easy Retrofitting
- All Aluminum Construction
- All Stainless Steel Hardware
- All Hardware *Included*
- Flashing Meets or Exceeds Minimum Standards of:
- NRCA, SMACNA, ARMA, & NFPA



Lag pull-out (allowable withdrawal) capacities (lbs) in typical lumber:

	Specific gravity	Lag screw specifications	
		5/16" shaft 3" thread depth	5/16" shaft 1" thread depth
Douglas Fir, Larch	0.50	798	266
Douglas Fir, South	0.46	705	235
Engelmann Spruce, Lodgepole Pine (MSR 1650 f & higher)	0.46	705	235
Hem, Fir	0.43	636	212
Hem, Fir. (North)	0.46	705	235
Southern Pine	0.55	921	307
Spruce, Pine, Fir	0.42	615	205
Spruce, Pine, Fir (E of 2 million psi and higher grades of MSR and MEL)	0.50	798	266

Shake Mounts



QMLC A 18" x 18" Shake Mount

Shake Mounts are structurally the same as the Composition Mounts. The flashing portion is larger because the exposure is larger. As the paper in a Shake Roof is the actual waterproofing, the Flashing must extend under one course of shakes plus extend under the paper of the next course of shakes to be waterproof.

Pool Mounts

Pool Mounts utilize a 1/4" lag bolt and our proprietary sealing method to insure quality flashing and securing of pool panels. Shown here in Bronze Anodized, they are also available in Clear Anodized as well as Mill Finish



QMPM B 9" x 12" Pool Mount

Conduit Mounts



QMCC A 9" x 12" Conduit Mount

Quickly and Simply...
Flashes the penetration of the conduit attachment. Allows water and debris to pass under. Lifts conduit off the roof relieving direct heat transfer from roofing to wiring.

Tile Mounts



QMCTM A Curved Tile Flashing With Mount(Aluminum) 18" x 18"
Designed to work with any Existing Curved Tile profile. All Aluminum - No Lead



QMFTM A Flat Tile Flashing With Mount (Aluminum) 12" x 17"
Designed to replace most Flat Concrete Tile profiles. No More Concrete Cutting or Drilling on the Roof. No more Awkward Custom Flashings. Fully compatible with:
Monier | Eagle | Hanson | Life Tile

Accessories



All Aluminum Mounts available in Mill Finish, **Bronze** or **Clear** Anodized

Tools:

- 1/2" Deep Socket
- Socket Adapter
- Roofing Bar
- Torque Wrench

All Specs, Instructions, Product Data is online at:
www.quickmountpv.com

Available through your preferred
Solar Distributor

Product List

QMSC x 12	Composition Mounts 12" x 12"
QMLC x 12	Shake Mounts 18" x 18"
QMPPM x 12	Pool Panel Mounts 9" x 12"
QMCC x 12	Conduit Mounts 9" x 12"
QMLCC x 12	Conduit Shake Mounts 12" x 18"
QMFTM x 12	Flat Tile Flashing w/ Mount 12" x 17"
QMCTM x 12	Curved Tile Flashing w/ Mount 18" x 18"
QMEXT-2.5 x 12	Height Extensions w/ Hardware 2 1/2"
QMEXT-3.25 x 12	Height Extensions w/ Hardware 3 1/4"
QMEXT-4.0 x 12	Height Extensions w/ Hardware 4"
QMRB 1	Roofing Bar 24"
QMDS-.50 1	1/2" Deep Socket
QMSA-.375 1	Socket Adapter
QMTW 1	Torque Wrench
QMHS-6 12	12 each 6" Hanger bolts S.S. w/ nuts, washers
QMHS-8 12	12 each 8" Hanger bolts S.S. w/ nuts, washers
QMHS-10 12	12 each 10" Hanger bolts S.S. w/ nuts, washers
QMHS-12 12	12 each 12" Hanger bolts S.S. w/ nuts, washers
Exchange x for	A (Mill Finish), B (Bronze Anodized), C (Clear Anodized)
Extension 12	Denotes that there are 12 units in a box
Extension 1	Denotes that there are 1 units in a box

Quick Mount PV®
Your ***Solution*** in Mounting Products
Solar • H₂O • Conduit • HVAC • Custom



**The ALL-IN-ONE
Waterproof Flashing & Mount
For Engineers & Installers
who DEMAND:**

**NRCA'S Standards & Best Practices
Code Compliance
Extended Lifespan
Labor Savings
No Roof Cutting
Works with ALL Racks**